




# FB 系列 Series

## 特点 Features

- 双极性，标准品，用于极性翻转或极性变换的电路中。  
Bi-polar Standard series, used in polarity reverse and change circuits.
- RoHS指令已对应完毕。  
Adapted to the RoHS directive.




## 主要技术性能 Specifications

项目 Items	特性 Characteristics																											
使用温度范围 Operating Temperature Range	-40~+105°C																											
额定电压范围 Rated Voltage Range	6.3~100V																											
标称电容量范围 Nominal Capacitance Range	0.47~4700μF																											
标称电容量允许偏差 Capacitance Tolerance	±20% (120Hz, +20°C)																											
正反向漏电流 Leakage Current	$I \leq 0.03CV + 3(\mu A)$ 2分钟 (at 20°C, after 2 minutes)																											
损耗角正切值 (tgδ) Dissipation Factor (+20°C, 120Hz)	<table border="1"> <thead> <tr> <th>UR (V)</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>100</th> </tr> </thead> <tbody> <tr> <td>tgδ</td> <td>0.28</td> <td>0.24</td> <td>0.22</td> <td>0.20</td> <td>0.15</td> <td>0.14</td> <td>0.13</td> <td>0.13</td> </tr> </tbody> </table>	UR (V)	6.3	10	16	25	35	50	63	100	tgδ	0.28	0.24	0.22	0.20	0.15	0.14	0.13	0.13									
UR (V)	6.3	10	16	25	35	50	63	100																				
tgδ	0.28	0.24	0.22	0.20	0.15	0.14	0.13	0.13																				
温度特性 Temperature Characteristics (Impedance ratio at 120Hz)	<table border="1"> <thead> <tr> <th>UR (V)</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>100</th> </tr> </thead> <tbody> <tr> <td>Z-25°C / Z+20°C</td> <td>4</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> </tr> <tr> <td>Z-40°C / Z+20°C</td> <td>10</td> <td>8</td> <td>6</td> <td>5</td> <td>4</td> <td>4</td> <td>3</td> <td>3</td> </tr> </tbody> </table>	UR (V)	6.3	10	16	25	35	50	63	100	Z-25°C / Z+20°C	4	3	2	2	2	2	2	2	Z-40°C / Z+20°C	10	8	6	5	4	4	3	3
UR (V)	6.3	10	16	25	35	50	63	100																				
Z-25°C / Z+20°C	4	3	2	2	2	2	2	2																				
Z-40°C / Z+20°C	10	8	6	5	4	4	3	3																				
耐久性 Load Life	105°C加额定电压2000小时 (每250小时反转极性一次) 恢复16小时后: After applying rated voltage for 2000 hours at 105°C (with the polarity inverted every 250 hours) and then resumed 16 hours: 电容量变化率 Capacitance change : ±20%初始测量值以内 ±20% of the initial measured value 漏电流 Leakage current : ≤初始规定值 Initial specified value 损耗角正切值 Dissipation factor : ≤2倍初始规定值 2times of the initial specified value																											
高温贮存 Shelf Life	+105°C, 1000小时贮存后, 恢复16小时后: After storage for 1000 hours at +105°C and then resumed 16 hours 电容量变化率 Capacitance change : ±20%初始测量值以内 ±20% of the initial measured value 漏电流 Leakage current : ≤2倍初始规定值 2times of the initial specified value 损耗角正切值 Dissipation factor : ≤2倍初始规定值 2times of the initial specified value																											

## 频率修正系数 Frequency Coefficient

F(Hz)	60	120	1K	≥10k
0.47 ~ 68	0.8	1	1.45	1.7
100 ~ 470	0.8	1	1.35	1.5
680 ~ 4700	0.8	1	1.2	1.3

## 外形图及尺寸表 Case Size Table



单位 Unit: mm

	D	5	6.3	8	10	12.5	16	18
F	2.0	2.5	3.5	5.0	5.0	7.5	7.5	7.5
d	0.5	0.5	0.5、0.6	0.6	0.6	0.8	0.8	0.8
αMAX	α < L < 20	1.5						
	α ≥ L ≥ 20	2.0						
βMAX	β < D < 20	0.5						
	β ≥ D ≥ 20	1.0						

## 尺寸 Dimensions

WV		6.3V(0J)		10V(1A)		16V(1C)		25V(1E)		35V(1V)	
		Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple
4.7	4R7									5×11	34
10	100					5×11	38	5×11	42	5×11	43
22	220			5×11	48	5×11	55	6.3×11	65	6.3×11	73
33	330	5×11	58	5×11	60	5×11	64	6.3×11	80	8×11.5	100
47	470	5×11	76	5×11	76	6.3×11	95	6.3×11	95	8×11.5	120
100	101	5×11	100	6.3×11	125	6.3×11	130	8×11.5	160	10×12.5	200
220	221	8×11.5	155	8×11.5	160	8×11.5	205	10×12.5	255	10×20	325
330	331	8×11.5	205	8×11.5	215	10×12.5	260	10×16	320	12.5×20	380
470	471	10×12.5	280	10×12.5	310	10×16	365	12.5×20	435	12.5×25	520
1000	102	10×16	360	10×20	445	12.5×20	535	12.5×25	580	16×25	780
2200	222	12.5×20	680	16×25	885	16×30	1050				
3300	332	16×25	1050	16×30	1150						
4700	472	16×30	1250								

WV		50V(1H)		63V(1J)		100V(2A)	
		Size	Ripple	Size	Ripple	Size	Ripple
0.47	R47	5×11	8	5×11	9	5×11	10
1	010	5×11	12	5×11	15	5×11	16
2.2	2R2	5×11	18	5×11	22	6.3×11	24
3.3	3R3	5×11	27	5×11	28	6.3×11	30
4.7	4R7	5×11	34	6.3×11	34	6.3×11	35
10	100	5×11	34	6.3×11	57	8×11.5	71
		6.3×11	52				
22	220	8×11.5	89	8×11.5	95	10×16	135
33	330	8×11.5	105	10×12.5	135	10×20	185
47	470	10×12.5	150	10×16	180	12.5×20	200
100	101	10×16	205	12.5×20	320	16×25	425
220	221	12.5×20	360	12.5×25	430	16×35	520
330	331	16×25	550	16×30	580		
470	471	16×30	580	18×35	760		

Size  $\phi D \times L$ (mm)  
 Maximum Allowable Ripple Current (mA rms) at 105°C 120Hz